

Model	IP-6620 (ColorPainter M-64s)
Print Head	High Frequency drop on demand piezo
Number of Nozzles	508 nozzles/head
Maximum Resolution	900 dpi
Maximum Media Width	1,626 mm (64")
Maximum Print Width	1,616 mm (63.6")
Printing Speed	3.5 to 66.5 smph (38 to 716 sfph)
Media Weight	Up to 50 kg (110 lbs)
Maximum Media Diameter	220 mm (8.7")
Margin Size	5 mm (1/5") on each edge (with rolled media, without edge guards)
Ink Type	Low-Odor and Eco Solvent: SX
Color	6 (C, M, Y, K, Lc, Lm) or 7 (C, M, Y, K, Lc, Lm, Gy)
Maximum Ink Capacity	1.5 liters per color
Media	PVC, Banner and other media designed for solvent printers.
Heater	3-way built-in heaters (Pre, Print, After)
Take-up Modes	Loose/Outer, Tension/Inner, Tension/Outer
Interface	USB 2.0
Power Source	200 to 240 VAC, 12A, 50Hz/60Hz
Power Consumption	2,880W or less
Operating Environment	15 - 30 °C (59 - 86 °F), 30 - 70 % RH (no condensation)
Storage Environment	5 - 35 °C (41 - 95 °F), 10 - 80 % RH (no condensation)
External Dimensions	3,095 (W) x 935 (D) x 1,247 (H) mm (122" x 37" x 49")
Weight	321 kg (708 lbs) or less without media and inks