

Specifications

Model	IP-7900-20 (ColorPainter H2-104s)	IP-7700-20 (ColorPainter H2-74s)
Print Head	High-frequency drop on demand piezo	
Number of Nozzles	508 nozzles × 8	
Resolution	360 dpi to 900 dpi	
Maximum Media Width	2,642 mm (104")	1,900 mm (74.8")
Maximum Print Width	2,632 mm (103.6")	1,890 mm (74.4")
Media Weight	Up to 120 kg (264 lbs.)	Up to 50 kg (110 lbs.)
Maximum Media Diameter	350 mm (13.8")	220 mm (8.7")
Margin Size	5 mm on each edge (with rolled media, without edge guards)	
Ink Type	Mild Solvent : EGO-GX	
Color	8 (C, M, Y, K, Lc, Lm, Gray & Light Gray) or 4 (C, M, Y, K) × 2	
Ink Capacity	1,500 ml per color	
Media	PVC, banner and other media designed for solvent printers.	
Heater	3-way built in heaters (Front/Print/Rear); Max temp. 70 °C	
Take-up modes	Loose/Inner, Loose/Outer, Tension/Inner, Tension/Outer	
Interface	USB 2.0	
Power Voltage	200 to 240 VAC, ±10%	
Power Consumption	Printer: 1440 W or less, Heater: 2880 W or less	
Operating Environment	15 - 30°C (59 - 86°F), 30 to 70% RH (no condensation)	
Storage Environment	5 - 35°C (41 - 95°F), 10 to 80% RH (no condensation)	
External Dimensions (W) x (D) x (H)	4126 × 1366 × 1513 mm (162" × 54" × 60")	3,383 × 1,275 × 1,511 mm (133" × 50" × 60")
Weight	600 kg (1,322 lbs.) or less	450 kg (992 lbs.) or less
Option	Mesh Printing Kit, Foot Switch, Scroller, Exhaust Attachments, Scroller Set (Shaft & 2 Flanges), Scroller Flange (2pcs/set), Exhaust Attachments	
Certificate	CE, CSA (NRTL/C), RoHS, Vietnam RoHS Tuân thủ hạn chế các chất nguy hại trong các thiết bị điện và điện tử.	