

High Speed Eco Solvent Printer

NEW**ColorPainter™ M-64s** - LCIS Model -**IP-6620 (ColorPainter M-64s LCIS model)**

Print Head	High Frequency drop on demand piezo
Number of Nozzles	508 nozzles/head
Maximum Resolution	900 dpi
Maximum Media Width	1,626 mm (64")
Maximum Print Width	1,616 mm (63.6")
Printing Speed	3.5 to 49.7 smph (38 to 535 sfph)
Media Weight	Up to 50 kg (110 lbs)
Maximum Media Diameter	220 mm (8.7")
Margin Size	5 mm (1/5") on each edge (with rolled media, without edge guards)
Ink Type	Low-Odor and Eco Solvent: WX
Color	6 (C, M, Y, K, Lc, Lm)
Ink Bottle Capacity	1 liter per color (2 bottles/box)
Ink Reservoir Capacity	Maximum 4.5 liters/color
Media	PVC, Banner and other media designed for solvent printers.
Heater	3-way built-in heaters (Pre, Print, After)
Take-up Modes	Loose/Outer, Tension/Inner, Tension/Outer
Interface	USB 2.0
Power Source	200 to 240 VAC, 12A, 50Hz/60Hz
Power Consumption	2,880W or less
Operating Environment	15 - 30 °C (59 - 86 °F), 30 - 70 % RH (no condensation)
Storage Environment	5 - 35 °C (41 - 95 °F), 10 - 80 % RH (no condensation)
External Dimensions	3,327(W) x 935(D) x 1247(H) mm (131" x 37" x 49")
Weight	360 kg (794 lbs) or less without media and inks

Option

IP6-010	Cutter unit (64")
IP7-013	Exhaust Attachment
IP5-261	2" flange

Consumables

IP6-241	WX Ink Yellow (2 bottles/set)
IP6-242	WX Ink Magenta (2 bottles/set)
IP6-243	WX Ink Cyan (2 bottles/set)
IP6-244	WX Ink Black (2 bottles/set)
IP6-245	WX Ink Light cyan (2 bottles/set)
IP6-246	WX Ink Light magenta (2 bottles/set)